



## Research article

## Actions to reduce carbon footprint in materials to healthcare buildings

Juan Pablo Carrasco-Amador<sup>\*</sup>, José Luis Canito-Lobo, Alberto Castaño-Liberal, Jesús Manuel Rodríguez-Rego, Manuel Matamoros-Pacheco

Department of Graphic Expression, School of Industrial Engineering, University of Extremadura, 06006 Badajoz, Spain



## ARTICLE INFO

## Keywords:

Greenhouse gases  
Carbon footprint  
Healthcare buildings

## ABSTRACT

Building sector is a major contributor to the emissions of pollutant gases, which are responsible for health-damaging effects of climate change. To quantify and reduce these emissions. This comparative study is presented between two buildings that could have a sanitary or any other type of use. Both buildings have similar characteristics, except for their structures, one made of metal and the other of concrete. The design, structural calculation and three-dimensional dimensioning were performed using Building Information Modeling (BIM). The budget and the product carbon footprint study were also carried out, to calculate the level of emissions of each building. The study determined higher emissions for the metal-structured building, with 621.234 tCO<sub>2</sub>/t<sub>material</sub> compared to 446.707 tCO<sub>2</sub>/t<sub>material</sub> for the concrete building. To reduce these emissions, measures related to the replacement of the previously selected materials, by other materials with lower emission rates and identical functionality were presented, such as the replacement of metal building roof polyurethane, or the composition of cement for the concrete building. Both actions represented a reduction of 84.61% CO<sub>2</sub> emissions for metal envelope building and 31.765% for the concrete structure. The results of this work will help to select more sustainable materials to use in the renovation of existing buildings, or in the construction of new buildings. For example, health-related buildings, currently in high demand, given the current pandemic situation caused by COVID-19.

## 1. Introduction

Reducing greenhouse gas (GHG) emissions, which are responsible for the effects related to climate change, is one of the biggest challenges facing our society [1, 2, 3, 4]. Despite exceptional decline in global emissions of carbon dioxide (CO<sub>2</sub>), one of the main GHGs, during 2020 caused by COVID-19 pandemic [5, 6], long-term projections point to an upward emissions scenario [7], which deviates from targets set by international [8] and national agencies [9].

Of all sectors causing GHG emissions, building and residential sectors [10, 11] are among the most responsible ones, with 36% of total net CO<sub>2</sub> emissions produced in Spain in 2018 [12,13]. Environmental impact of buildings occurs at different stages of their life cycle: planning, construction, operation, renovation and demolition, with operation stage accounting for largest percentage, with approximately 85% of GHG emissions [14, 15], this figure may vary from country to country [16], e.g. 43% in the United States and more than 50% in China [17]. However, the impact of building materials is coming into the spotlight, due to the publication of more restrictive policies by administrations, to promote energy savings in buildings [18, 19].

In order to minimize the environmental impact of the building sector and allow it to evolve in line with sustainability, tools such as carbon footprint measurement have been developed [20, 21, 22], defined as the amount of CO<sub>2</sub> equivalent emissions caused directly and indirectly by an activity, or as the total amount of GHG emissions during the life cycle of a product or service. Life Cycle Assessment (LCA) [23], is one of the widely accepted tools for calculating carbon footprint [24], especially at the product level [25].

There are numerous studies in the literature on the carbon footprint assessment in buildings, which can be classified into two main groups: those aimed at assessing GHG emissions during the extraction of raw materials, the manufacture of components and building materials and those aimed to the transport of materials to the construction site. As an example, Li, X-J. et al. [21], researched the carbon footprint in the materialization phase of precast concrete buildings using a calculation model combined with Building Information Modelling (BIM) technology. The results revealed a significant reduction of carbon footprint per unit area in precast concrete projects. In a similar study, Li, X-J. et al. [22] researched the carbon footprint at the construction stage of precast concrete piles using the LCA method, yielding carbon emissions data for

<sup>\*</sup> Corresponding author.

E-mail address: [jpcarrasco@unex.es](mailto:jpcarrasco@unex.es) (J.P. Carrasco-Amador).

the construction machinery of 73% of the total, with a strong linear relationship between pile foundation area, foundation cost, number of foundations and total carbon emission during the construction. Following the line of the previous authors regarding the impact of concrete materials, Xiao, J. et al. [26] researched the carbon footprint of two identical high-rise buildings, one made of recycled aggregate concrete and the other of natural aggregate concrete. In the results, the recycled aggregate concrete achieved a decrease of up to  $2.175 \times 10^5$  kg CO<sub>2</sub> in carbon footprint, compared to natural aggregate concrete. There are also works which are not linked to the more traditional materials used in construction, with the aim of investigating new possibilities for reducing the carbon footprint at the material manufacturing stage, such as the research by Scrucca, F. et al. [27], about the use of sustainable materials, such as hemp, due to its good hygrothermal and acoustic insulation properties.

On the other hand, there are works to evaluate GHG emissions from the daily energy consumption of buildings in their operational phase (air conditioning, water supply, lighting, etc.). As an example, Gamarra, A.R. et al. [28] analysed the activities with energy, material and water requirement of two school buildings located in hot climates, assessing the carbon footprint through LCA. They quantified the effects of different improvement measures, such as the implementation of renewable energy sources and the optimisation of energy use, based on energy efficiency measures, by proposing modifications to the luminaries. Also related to the education sector, Clabeaux, R. et al. [29] evaluated the carbon footprint of a university campus using the simplified LCA tool and found the main sources of GHG emissions to be electricity generation (41%), car travel (18%) and steam generation (16%). Similarly, Onat N.C. et al. [30] obtained a carbon footprint percentage for electricity generation of 48% and more than 10% for commuting in residential and commercial buildings in the USA. Kairies-Alvarado, D. et al. [19] also analysed how to reduce the carbon footprint in the operation phase of public buildings and found that it is possible to reduce it by 82%.

The first works (carbon footprint assessment in the construction phase), present the difficulty of quantifying a large amount of data, due to the diversity of materials and machinery used. The second (carbon footprint assessment in the operation phase) present the complexity of quantifying energy consumption, due to the different lifestyles and multiple uses of the building. To solve these problems, the use of new and powerful tools is required [25].

Literature includes works on the carbon footprint of buildings of different types, but in line with the objectives of this study, it is worth highlighting the importance of large buildings, destined for example to the hospital, health, or residential area for the care of the elderly. With the current health crisis caused by the pandemic, the need for the construction of this type of building has increased [31], leading to a significant contribution of GHGs in the different stages of their life cycle [32, 33, 34, 35], focusing attention on the large amount of material resources invested in the construction stage, due to the large size of these buildings in most cases.

Considering therefore as valid this work for its application in buildings for medical, health or any other use, such as teaching or residential for the elderly. As long as it involves the execution of large buildings.

In order to contribute to the simplification of carbon footprint calculation methods through technological tools and with the aim of reducing the main CO<sub>2</sub> contributions of buildings associated with their construction and use, two virtual models of typical buildings of large dimensions valid for various uses.

The first one with a concrete structure and the second one with a steel structure, in order to represent the current scene of these buildings, using the CYPECAD software, “*Generador de porticos*” y CYPE3D 2017 version (CYPE Ingenieros S.A.) [36] for their structural calculation and Autodesk Revit 2020 (Autodesk Inc.) [37] for their subsequent 3D dimensioning using BIM. A comparative study was made of the carbon footprint of both, in the construction and operation stages, in relation to energy consumption, finally determining which type of building is a greater

emitter of CO<sub>2</sub>, and establishing a series of measures to be adopted to achieve a reduction in these emissions. Unlike other similar works, where the carbon footprint is only analysed in one of the phases of the building’s life cycle and/or where existing buildings are analysed, the results of which may be difficult to extrapolate to new buildings, these virtual models are presented, the configuration of which can be extrapolated to healthcare buildings or buildings of other types.

## 2. Methodology

In order to provide the final measures aimed at reducing the carbon footprint of materials used in the construction of buildings for sanitary use, a comparative study of product carbon footprint (PCF) was previously carried out, based on the methodology for the quantification of PCF, established in the standard UNE-EN ISO 14067:2018 [38].

To carry out this study, the structures, both metallic and concrete, were calculated with the CYPECAD, “*Generador de porticos*” and CYPE3D 2017 version (CYPE Ingenieros S.A.) software [36]. Subsequently, a 3D dimensioning of the buildings was carried out using BIM, with the Autodesk Revit 2020 software (Autodesk Inc.) [37], in order to quantify all the materials used in the construction of the building.

Budgets were drawn up to quantify the costs of the two buildings and an inventory was drawn up with the emissions of each of the materials and items that make up the building, with the aim of identifying which of these were the most polluting, as well as an overall calculation of the emissions of each building. The emissions corresponding to the transport of materials to the building, from a established distance of 100 km, were also calculated.

In the end, with the HCP quantification study and the budgets, the improvements in terms of structural modifications and change of materials of the building elements were established, to achieve the carbon footprint reduction target.

The different phases of this work are described below.

### 2.1. Definition of standard buildings

The structural calculations of the buildings were carried out on the basis of the Technical Building Code, in its Basic Document on Structural Safety [39], establishing the location in the city of Badajoz (06006 – España) and their use as a health care facility (hospital, health centre, or similar). The structural characteristics of both buildings are detailed in Table 1.

#### 2.1. 3D design and materials



Autodesk Revit was used to make the three-dimensional models of the buildings in order to get an overview of both (Figure 1A and B), to quantify the materials used in their construction, and later, to prepare budgets and an inventory of CO<sub>2</sub> emissions.



As for the materials used, those most used today in this type of construction were selected, obtaining calculations that are representative of reality. The list of materials used for both buildings is detailed in Table 2.

### 2.2. Measurements and budget

The methodology followed was, firstly, to calculate the measurements of the structural elements, using CYPE - Archimedes software, and those of the construction elements, using Autodesk Revit software. Later, the total budget for both buildings, with their structure and construction elements, was calculated. For this purpose, the unit prices of each item were taken from the CYPE price generator and multiplied by the measurements obtained to calculate the Material Execution Budget (MEB). The comparative manufacturing cost of both buildings will be detailed in the results section.

**Table 1.** Structural characteristics of buildings.

|                        | Concrete building   | Metal building   |
|------------------------|---|--|
| Structural description | Reinforced concrete with steel bars or meshes                                     | Rolled steel. 6 portal frames and 5 spans  |
| Sizes                  | 27 × 18 × 6 m   | 27 × 18 × 6 m  |
| Foundations            | Insulated feets with tie beams  | Insulated feets with tie beams   |
| Pillars                | 36 units, 6 × 0.30 × 0.30 m   | 30 units: 2 of 8 m (IPE 200), 12 of 7.5 m (IPE 300), 4 of 7.75 m (IPE 180) y 12 of 3 m (IPE 240) |
| Beams                  | 0.5 × 0.3 m   | 50 units: IPE 200 and IPE 240  |
| Frameworks             | Prestressed beam  | -  |
| Mezzanine floor        | Yes, at a height of 3 m   | Yes, at a height of 3 m  |
| Roof                   | Flat roof, 3% slope   | Gable roof with a 22.2% slope, 8 m ridge and 6 m wall height. 10.8 m straps (IPE 100).           |
| Picture                |  |               |



**Figure 1.** A) Autodesk Revit 3D view of the concrete frame building. B) Autodesk Revit 3D view of the steel structure building.

**Table 2.** Materials selected for both buildings.

|                     |  |
|---------------------|--|
| Frameworks          | Concrete floor, 0,05 mm thick polyethylene separating sheet and 10 cm thick mass concrete floor screed |
| Floors              | Ceramic tiles of glazing stoneware   |
| External enclosures | Metal building: alveolar plates of prestressed concrete<br>Concrete building: thermoclay block         |
| Internal enclosures | Double hollow ceramic bricks, for cladding, 7 cm thick   |
| Roofs               | Metal building: polyurethane Sandwich type panels<br>Concrete building: conventional fixed flooring    |
| False ceiling       | Only in metal building: plaster plates with ribbing  |
| Doors               | Aluminium and wood   |
| Windows             | “Aluplast ideal 4000 cl”   |

### 2.3. Calculation of total CO<sub>2</sub> emissions

After carrying out the structural calculations of the buildings, the choice of materials and the budgets, the total emissions in tonnes of CO<sub>2</sub> equivalent (tCO<sub>2</sub>e) that would be released into the atmosphere in both buildings were calculated. For this purpose, different material emission tables were used [40] detailing the densities of each material and the tCO<sub>2</sub>e per tonne of material manufactured. The tables are based on the “Cradle-to-gate” methodology, which establishes the limits of the system in terms of emissions, measured up to the exit of the factory. The

emissions associated with the transport of the materials were also calculated, establishing a standard distance for all of them of 100 km. The total number of tonnes to be transported, the tonnes that can be transported by each type of vehicle and their emissions were calculated. Finally, the emissions associated with the use of the building with respect to energy consumption were calculated. The results obtained from the product carbon footprint study will be detailed in the results section.

### 2.4. Actions for carbon footprint reduction

After the total CO<sub>2</sub> emission data were obtained, measures were developed to reduce the carbon footprint, such as: replacement of the sandwich roof insulation, change of the cement composition, replacement of the material of the interior partitions and study of the material for the exterior windows. The influence of these measures on the results was evaluated and conclusions were drawn.

## 3. Results and discussion

### 3.1. Building cost comparison

In order to quantify the cost of construction of the buildings and to assess how it could vary through the application of carbon footprint reduction measures, a comparison of the budgets of the structures (Figure 2a) and of the building constructive elements was made, Figure 2b.




Figure 2. a) Comparison of structure cost – b) Comparison of constructive elements.

The comparison of the structures shows a higher cost of pillars and beams for the steel structure, the costs of the foundations are similar, due to the tie beams and the type of foundations used have been similar. As for the frameworks, the price of the concrete structure is higher due to the roof slab, which does not exist for the steel structure. The structural cost of the concrete building is €4436.42 higher than the metal building.

The comparison of construction elements shows a similar cost of enclosures, partitions and floors, due to the similarity of the materials used. The cost of the flat roof of the concrete building is very high due to its unit price and represents the biggest difference between the two

buildings. The doors and windows differ only because they are larger in the concrete building. The cost of the construction elements of the concrete building is € 10,664.60 higher than the metal building.

### 3.1. CO<sub>2</sub> total emissions

After inventorying the materials in the measurements and budgets section, the tonnes of CO<sub>2</sub> emitted per tonne of material (tCO<sub>2</sub>/t<sub>material</sub>) were calculated and classified according to each type of construction element: quarry materials, concrete blocks, metals, glasses, plastics, woods, insulations, gypsums, concretes and energy.

Table 3. Total CO<sub>2</sub> emission of the metal building broken down by materials.

| Metal structure building   |                          |  |                              |  |                                     |
|--|--------------------------|--|------------------------------|--|-------------------------------------|
| Type of construction material  | Volume (m <sup>3</sup> ) | Volume used specifications   | Total weight of material (t) | Emissions rate (tCO <sub>2</sub> e/t <sub>material</sub> ) | Total emissions (tCO <sub>2</sub> ) |
| Concrete cleaning layer HL-150/B/20 (Concrete)                               | 48,600                   | 486 m <sup>2</sup> with thickness 0.1 m  | 93,832                       | 0.170  | 15,970                              |
| Reinforced concrete foundation footing (Concrete)                            | 17,929                   | 17.929 m <sup>3</sup> concrete footing   | 34,616                       | 0.170  | 5892                                |
| Reinforced concrete tie beam, made of concrete (Concrete)                    | 36,722                   | 36.722 m <sup>3</sup> of concrete in tie beam  | 70,899                       | 0.170  | 12,067                              |
| S275JR steel in pillars, with single parts made of IPE profiles (Steel: bar) | x                        | 5150.4 kg of steel in pillars  | 5150                         | 1.400  | 7211                                |
| S275JR steel in beams, with single parts made of IPE profiles (Steel: bar)   | x                        | 16,941.56 kg of steel in beams   | 16,942                       | 1.400  | 23,718                              |
| Internal enclosure sheet of ceramic brick masonry for cladding (Brick)       | 31,920                   | 456 m <sup>2</sup> with thickness 0.07 m   | 60,648                       | 0.240  | 14,556                              |
| Heavy prestressed concrete hollow-core slab façade (concrete block)          | 111,690                  | 657 m <sup>2</sup> with thickness 0.17 m   | 156,366                      | 0.107  | 16,731                              |
| Sloping roof of insulated sandwich panels (Steel and Polyethylene)           | 4.98 + 149.40            | 498 m <sup>2</sup> of panel sandwich: thickness 0.30 (insulation) + 0.01 (sheet metal) | 176,292                      | 1.38 + 2.54  | 402,723                             |
| Reinforced concrete structure. Not including impact of pillars (Concrete)    | 92,875                   | 371.50 m <sup>2</sup> with thickness 0.25 m  | 179,314                      | 0.170  | 30,519                              |
| Stone paving (Limestone)   | 97,200                   | 486 m <sup>2</sup> with thickness 0.2 m  | 213,840                      | 0.090  | 19,246                              |
| Polyethylene separator film (Polyethylene)                                   | 0.024                    | 486 m <sup>2</sup> with thickness 0.00005 m  | 0.022                        | 2.540  | 0.057                               |
| Concrete floor (Concrete)  | 48,600                   | 486 m <sup>2</sup> with thickness 0.1 m  | 93,832                       | 0.170  | 15,970                              |
| Adhesive-fixed ceramic tile flooring (General ceramics)                      | 4860                     | 486 m <sup>2</sup> with thickness 0.01 m   | 11,664                       | 0.700  | 8165                                |
| Continuous plasterboard false ceilings (Plaster)                             | 4860                     | 486 m <sup>2</sup> with thickness 0.01 m   | 6318                         | 0.130  | 0.821                               |
| Inner hinged door, wooden (203 × 82.5 × 4 cm) (General wood)                 | 0.804                    | 12 doors of 2.03 × 0.825 × 0.04 m  | 0.402                        | 0.310  | 0.125                               |
| Entrance door to the building, aluminium, "CORTIZO" (Aluminium)              | 0.608                    | 2 doors of 2.60 × 2.60 × 0.45 m  | 1643                         | 9.160  | 15,047                              |
| Casement window (General PVC)  | 7591                     | 34 windows of 1.83 × 1.22 × 0.10 m   | 10,475                       | 3.100  | 32,474                              |
| <b>TOTAL</b>   |                          |  | <b>1,132,255</b>             | <b>0.549</b>   | <b>621,290</b>                      |

To show the emission data obtained in a summarised form and classified according to each type of building, the following tables were prepared: Table 3 shows total CO<sub>2</sub> emission of the metal building, broken down by materials and, Table 4, Total CO<sub>2</sub> emission of the concrete building, broken down by materials.

For emissions related to transport, an average distance for all materials of 100 km was taken. This estimation was made considering that some materials would have to be supplied from further away, while others could be supplied from the location of the building construction site itself. The total number of tonnes to be transported, the tonnes that can be transported by each type of vehicle and the emissions of these vehicles were calculated.

It was, therefore, observed that CO<sub>2</sub> emissions would be lower if more goods could be transported per trip. The transport-related emissions are shown in Table 5 .

Table 5 shows that by increasing the number of materials transported per vehicle by 10 units, CO<sub>2</sub> emissions to the atmosphere were more than halved.

Once the total emissions data was obtained, a comparison was made between the two buildings, in order to determine which type of structure leads higher CO<sub>2</sub> emissions (see Table 6).

The data revealed that, in terms of structure, the biggest difference in emissions was in the frameworks, because the concrete structure has an extra framework for the roof, which does not exist in the metal structure.

**Table 4.** Total CO<sub>2</sub> emission of the concrete building broken down by material.

| Concrete structure building   |                          |  |                              |   |                                     |
|---|--------------------------|--|------------------------------|---|-------------------------------------|
| Type of construction material   | Volume (m <sup>3</sup> ) | Volume used specifications                     | Total weight of material (t) | Emissions rate (tCO <sub>2</sub> e/ t <sub>material</sub> ) | Total emissions (tCO <sub>2</sub> ) |
| Concrete cleaning layer HL-150/B/20 (Concrete)                              | 14,046                   | 140,46 m <sup>2</sup> with thickness 0,10 m    | 27,119                       | 0.170   | 4616                                |
| Reinforced concrete foundation footing (Concrete)                           | 31,081                   | 31.081 m <sup>3</sup> concrete footing         | 60,008                       | 0.170   | 10,213                              |
| Reinforced concrete tie beam (Concrete)                                     | 10,320                   | 10.32 m <sup>3</sup> of concrete in tie beam   | 19,925                       | 0.170   | 2391                                |
| Reinforced concrete centring beam (Concrete)                                | 24,670                   | 24.67 m <sup>3</sup> of concrete centring beam | 47,630                       | 0.170   | 8107                                |
| Reinforced concrete structure (Concrete)                                    | 185,793                  | 743.17 m <sup>2</sup> with thickness 0.25 m    | 358,710                      | 0.170   | 61,052                              |
| Reinforced concrete, straight, dropped beam (Concrete)                      | 83,860                   | 83.86 m <sup>3</sup> of concrete in beams      | 161,909                      | 0.170   | 27,557                              |
| Reinforced concrete stair slab (Concrete)                                   | 2370                     | 15,8 m <sup>2</sup> with thickness 0.15 m      | 4576                         | 0.170   | 0.779                               |
| Reinforced concrete rectangular or square cross-section pillar (Concrete)   | 17,496                   | 17.496 m <sup>2</sup> of concrete in pillars   | 33,780                       | 0.170   | 5749                                |
| Interior partition sheet made of ceramic brick masonry for cladding (Brick) | 28,840                   | 412 m <sup>2</sup> with thickness 0.07 m       | 54,796                       | 0.240   | 13,151                              |
| External leaf of thermoclay block masonry (General ceramics)                | 117,120                  | 488 m <sup>2</sup> with thickness 0.24 m       | 281,088                      | 0.700   | 196,762                             |
| Flat, non-ventilated, walkable roof with fixed screed (Concrete)            | 58,320                   | 486 m <sup>2</sup> with thickness 0.12 m       | 112,598                      | 0.170   | 19,164                              |
| Stone paving (Limestone)  | 97,200                   | 486 m <sup>2</sup> with thickness 0.2 m        | 213,840                      | 0.090   | 19,246                              |
| Polyethylene separator film (Polyethylene)                                  | 0.024                    | 486 m <sup>2</sup> with thickness 0.00005 m    | 0.022                        | 2.540   | 0.057                               |
| Concrete floor (Concrete)   | 48,600                   | 486 m <sup>2</sup> with thickness 0.1 m        | 93,832                       | 0.170   | 15,970                              |
| Adhesive-fixed ceramic tile flooring (General ceramics)                     | 4860                     | 486 m <sup>2</sup> with thickness 0.01 m       | 11,664                       | 0.700   | 8165                                |
| Interior hinged door, wooden (General wood)                                 | 0.737                    | 11 doors of 2.03 × 0.82 × 0.04 m               | 0.369                        | 0.310   | 0.114                               |
| Entrance door to building, aluminium (Aluminium)                            | 0.608                    | 2 doors of 2.60 × 2.60 × 0.045 m               | 1643                         | 9.160   | 15,047                              |
| Double casement window (general PVC)  | 6698                     | 30 windows of 1.83 × 1.22 × 0.10 m             | 9243                         | 3.100   | 28,653                              |
| Double casement window (general PVC)  | 2084                     | 14 windows of 1.22 × 1.22 × 0.10 m             | 2876                         | 3.100   | 8914                                |
|   |                          | <b>TOTAL</b>                                   | <b>1,495,626</b>             | <b>0.299</b>  | <b>446,707</b>                      |

**Table 5.** CO<sub>2</sub> emissions related to the transport of materials from buildings.

| Concrete building |   |   |  |                                    |                          |                                     |
|-------------------|---|---|--|------------------------------------|--------------------------|-------------------------------------|
| Distancia (km)    | Means of transport (quantity that can be transported) | Emissions rate (gCO <sub>2</sub> e/ passenger•km) | Emissions per vehicle (tCO <sub>2</sub> e) | Total amount to be transported (t) | Required vehicles (unit) | Total emissions (tCO <sub>2</sub> ) |
| 100               | Diesel van (3,5 t)                                    | 250.92  | 25.09                                      | 659.76                             | 189.00                   | <b>4,742.44</b>                     |
| 100               | Diesel truck (34 t)                                   | 1011.06   | 101.11                                     | 659.76                             | 189.00                   | <b>2022.12</b>                      |
| Metal building    |   |   |  |                                    |                          |                                     |
| Distancia (km)    | Means of transport (quantity that can be transported) | Emissions rate (gCO <sub>2</sub> e/ passenger•km) | Emissions per vehicle (tCO <sub>2</sub> e) | Total amount to be transported (t) | Required vehicles (unit) | Total emissions (tCO <sub>2</sub> ) |
| 100               | Diesel van (3.5 t)                                    | 250.92  | 25.09                                      | 575.54                             | 165.00                   | <b>4140.23</b>                      |
| 100               | Diesel truck (34 t)                                   | 1011.06   | 101.11                                     | 575.54                             | 17.00                    | <b>1718.80</b>                      |



**Table 6.** Comparison between the emissions of the two buildings.

| Structure emissions (tCO <sub>2</sub> /t <sub>material</sub> ) |              |               | Constructive elements emissions (tCO <sub>2</sub> /t <sub>material</sub> ) |               |               |
|--|--------------|---------------|--|---------------|---------------|
| Item   | Metal        | Concrete      | Item   | Metal         | Concrete      |
| Foundation, frameworks and stairs (Common in both)             | 64.44        | 88.15         | External enclosure   | 16.73         | 196.76        |
| Pillars and beams  | 30.92        | 33.30         | Roof   | 402.72        | 19.16         |
|  |              |               | Other elements (Common in both)  | 106.40        | 109.31        |
| <b>Total</b>   | <b>95.37</b> | <b>121.46</b> |  | <b>525.85</b> | <b>325.24</b> |

Although the emissions rate of steel beams and pillars is much higher than those of concrete, the emissions are similar, due to the smaller amount of steel required in the construction of metal structures. Regarding the construction elements, the biggest difference lies in the external enclosures and the roof. Sandwich panel and thermoclay block are highly polluting and account for a high percentage of emissions. As for the rest of the construction elements, there are hardly any difference, as the same materials have been used and in similar quantities, with a slight appreciable difference in the use of more or less material depending on the square metres. This comparison shows that the building type with the highest emissions is the metal structure, with 621.234 tCO<sub>2</sub>/t<sub>material</sub>, compared to 446.707 tCO<sub>2</sub>/t<sub>material</sub> for the concrete building.


### 3.2. Carbon footprint reduction actions

#### 3.2.1. Sandwich panel insulation replacement

As a first action, it was proposed to replace the insulation type of sandwich roof, as it was responsible for 64.85% of the total emissions of the metal building. The sandwich roof is composed of two galvanised steel sheets on the outside and polyurethane insulation on the inside. In order to reduce the value of these emissions without altering the functionality, the polyurethane was replaced by rockwool. Rockwool offers characteristics such as: fire protection, thermal insulation, impermeability and good acoustic insulation. Its lifespan can be compared to that

**Table 7.** Results of emission reductions in roof insulation.

| Results of emission reductions in roof insulation |            |   |   |  |                |                         |
|---|------------|---|---|--|----------------|-------------------------|
| Insulation type                                   | Weight (t) | Material emissions (tCO <sub>2</sub> /t <sub>material</sub> ) | Total CO <sub>2</sub> emissions (tCO <sub>2</sub> ) | CO <sub>2</sub> emissions reductions (%) | Total cost (€) | Total cost increase (%) |
| POLYURETHANE                                      | 137,45     | 2,54  | 402,72  | 84,61                                    | 13,212.04      | 54,5                    |
| ROCKWOOL  | 7,47       | 1,12  | 61,97   |  | 20,413.02      |                         |



**Figure 3.** Change in budget and CO<sub>2</sub> emissions due to material changeover.

**Table 8.** Estándar concrete components (94% clinker).

| Components       | Proportion (%) | Density (t/m <sup>3</sup> ) | Emissions (tCO <sub>2</sub> e/t <sub>material</sub> ) |
|------------------|----------------|-----------------------------|---|
| Portland cement  | 13.34          | 1.50                        | 0.95  |
| Water            | 6.66           | 1.00                        | 0.00000034  |
| Sand             | 26.67          | 2.24                        | 0.0051  |
| Gravel           | 53.33          | 2.00                        | 0.079   |
| Total (concrete) | 100            | 1.93                        | 0.170   |

**Table 9.** Modified concrete components (50 % clinker).

| Components       | Proportion (%) | Density (t/m <sup>3</sup> ) | Emissions (tCO <sub>2</sub> e/t <sub>material</sub> ) |
|------------------|----------------|-----------------------------|---|
| Cement 50-50     | 13.34          | 1.50                        | 0.544   |
| Water            | 6.66           | 1.00                        | 0.00000034  |
| Sand             | 26.67          | 2.24                        | 0.0051  |
| Gravel           | 53.33          | 2.00                        | 0.079   |
| Total (concrete) | 100            | 1.93                        | 0.116   |

of a building, as it does not degrade over time. In addition, the final product contains a high percentage of recycled content, which can vary between 70% and 90% [41].


Table 7 details the variation of the data with material substitution. The emission rate of rock wool is 1.12 tCO<sub>2</sub>/t<sub>material</sub> compared to 2.54 tCO<sub>2</sub>/t<sub>material</sub> for polyurethane insulation. This, together with the fact that its density is up to 18 times lower, reduces emissions from the initial 402.72 tCO<sub>2</sub> emitted by the roof, to 61.97 tCO<sub>2</sub> with the rock wool, keeping constant the 53.6 tCO<sub>2</sub> associated with the metal sheets of the sandwich panel. After applying this measure, there was a reduction in roof emissions of 84.61%. Variation data for both CO<sub>2</sub> emissions and the impact on the EMP are shown in Table 7. Figure 3 shows the change in budget and CO<sub>2</sub> emissions due to material changeover.

#### 3.2.2. Cement composition change of the concrete structure

Cement results from the decomposition of limestone and other calcareous materials. This decomposition produces clinker, a granular

**Table 10.** Results of the modification of concrete components.

| Concrete type | Emissions (tCO <sub>2</sub> e/t <sub>concrete</sub> ) | Amount of concrete used | Concrete building emissions (tCO <sub>2</sub> ) | Reduction of CO <sub>2</sub> emissions |
|---------------|---|-------------------------|---|--|
| Traditional   | 0.170   | 920,086                 | 156,415   | 49,685                                 |
| Modified      | 0.116   | 920,086                 | 106,730   |  |



**Figure 4.** Variation of emission rate with respect to clinker variation in concrete.

material which is the main component of common cement, known as Portland cement. Portland cement in Spain, used in most buildings, contains approximately 94–95% clinker, being the remaining 5% other additives. The problem of cement production lies in the production process of obtaining the clinker, which requires a heating process of

about 1400 °C, in which carbon is released, which when combined with air produces CO<sub>2</sub>, which is emitted into the atmosphere. To these emissions must be added those emitted by the kilns, which use large amounts of energy to reach these temperatures and therefore also generate CO<sub>2</sub>.

The remaining percentage of cement formation is usually done with granulated blast furnace slag, which determines the production yield and can achieve a higher ecological benefit by using a lower percentage of clinker, thus achieving lower CO<sub>2</sub> emissions and lowering the costs of energy generation for cement production. Maintaining at all times the strength requirements of the concrete [42, 43].

After analysing the emissions associated with cement, a change in cement composition was considered to study the potential benefits, in terms of emission and cost reductions. To this end, a study was carried out with a 94% clinker composition in the cement, which is detailed in Table 8.


Subsequently, modifications were made, starting with 94% Portland cement clinker, and the characteristics and emissions of the new concrete were obtained, starting with 50% Portland cement, as detailed in Table 9.

After the modification of the cement composition, see Table 10, a new concrete was obtained with a reduction in CO<sub>2</sub> emissions of 31.765%, a percentage that is relevant considering the large quantities of concrete used in construction. The building with a concrete structure, with this change in composition, went from emitting 156.415 to 106.73 tonnes of CO<sub>2</sub>, which means a total of 49.685 tonnes less CO<sub>2</sub> emitted.

Figure 4 shows the variation of the concrete emission rate when the clinker percentage is varied. The variations were made from 94%, the common percentage of Portland cement, to 35%, as the minimum percentage to which the clinker can be reduced while maintaining the properties of the concrete [44].

**3.2.3. Replacement of internal enclosures material**

The reduction of emissions through the replacement of the building’s interior partition materials was also studied, analysing the available options on the market, and comparing them with each other. The initial material used was ceramic brick masonry, as it is the most common material currently used in this type of construction elements. The total emissions corresponding to the partitioning of this material are 13.13 tonnes of CO<sub>2</sub> [45].



**Figure 5.** Variation in budget and emissions by type of internal enclosures.

A comparison of this material was carried out with: tongue and groove steel partition panels with rockwool insulation and glass fibre reinforced gypsum board interior partitions. The comparative study revealed the results shown in Figure 5.

From the study it can be extracted that the sectorial steel and rockwool panels present a decrease in CO<sub>2</sub> emissions regarding to ceramic bricks of 2.82% and an increase in the MEB of a significant 7.02%, and this solution can be rejected due to the large increase in the MEB. On the other hand, plaster panels represent a reduction in CO<sub>2</sub> emissions with respect to ceramic bricks of 2.24%, a smaller reduction than that produced by steel and rockwool panels, and an increase in the MEB of 2.08%, this being an assumable increase and, therefore, considering plaster panels as an useful material to replace traditional ceramic bricks.

#### 4. Conclusions

A comparative study was carried out between two similar buildings. They can be used for sanitary use or for any other use. One of the buildings in concrete structure and the other in a metal structure, to determine the carbon footprint of the materials used.

To determine the carbon footprint, the buildings were first designed, and their structures calculated. A 3D dimensioning of the buildings was carried out using BIM, with which the materials used in the construction of the building were quantified. Budgets were drawn up to quantify the costs of the two buildings and an inventory was drawn up with the emissions of each of the materials and items that make up the building.

The results revealed that the building type with the highest emissions is the one with metal structure, with 621.290 tCO<sub>2</sub>/t<sub>material</sub>, compared to 446.707 tCO<sub>2</sub>/t<sub>material</sub> for the concrete building.

Analysing the results from a more localised perspective in the purely structural elements (foundations, pillars, and beams), it should be noted that metal structures are less polluting than concrete structures. Although steel has higher emissions rate than concrete, with a rate of 1.4 tCO<sub>2</sub>/t<sub>steel</sub> and 0.17 tCO<sub>2</sub>/t<sub>concrete</sub>.

This is because metal structures use fewer tonnes of this material and are quicker to build, so overall they have a lower environmental impact.

After knowing the emissions data, measures were proposed to reduce these emissions through the replacement of the materials used. Such as the replacement of the insulation material of the sandwich panels used for the roof of the metal building, which resulted in a reduction of 84.6% in roof emissions and an increase of 4.64% in the MEB.

The composition of the cement used in the concrete structure was also modified, decreasing the percentage of clinker to 50%. Which generated a decrease in CO<sub>2</sub> emissions related to the concrete structure of 31.765%.

Finally, the substitution of interior enclosure materials was studied, comparing ceramic brick with steel and rockwool panels and plaster panels. With this latter one being considered as the best option for replacing ceramic brick in terms of emissions/price reduction.

As future lines of improvement, a study is considered including more emission reduction measures such as: supplying heating through renewable sources, supplying sanitary hot water through renewable sources such as geothermal energy, the use of biomass in boilers, establishing external thermal insulation systems, the replacement of metal roofs with wood and the use of special low emissivity or solar control glass.

#### Declarations

##### Author contribution statement

Juan Pablo Carrasco-Amador, Alberto Castaño-Liberal, Manuel Matamoros-Pacheco: Conceived and designed the experiments; Performed the experiments; Analyzed and interpreted the data; Contributed reagents, materials, analysis tools or data; Wrote the paper.

José Luis Canito-Lobo, Jesús Manuel Rodríguez-Rego: Performed the experiments; Contributed reagents, materials, analysis tools or data; Wrote the paper.

##### Funding statement

This work was supported by Junta de Extremadura and ERDF (GR21068, and GR21006).

##### Data availability statement

Data included in article/supp. material/referenced in article.

##### Declaration of interest's statement

The authors declare no conflict of interest.

##### Additional information

No additional information is available for this paper.

##### Acknowledgements

The authors are supported by Junta de Extremadura and ERDF "A way of making Europe", through the Project GR21068 and Project GR21006.

##### References

- [1] C. Bellard, C. Bertelsmeier, P. Leadley, W. Thuiller, F. Courchamp, Impacts of climate change on the future of biodiversity, *Ecol. Lett.* 15 (2012) 365–377.
- [2] J.A. Patz, D. Campbell-Lendrum, T. Holloway, J.A. Foley, Impact of regional climate change on human health, *Nature* 438 (2005) 310–317.
- [3] D. Touma, S. Stevenson, F. Lehner, S. Coats, Human-driven greenhouse gas and aerosol emissions cause distinct regional impacts on extreme fire weather, *Nat. Commun.* (2021) 12.
- [4] L. Kuai, K.W. Bowman, H.M. Worden, R.L. Herman, S.S. Kulawik, Hydrological controls on the tropospheric ozone greenhouse gas effect, *Elementa* 5 (2017).
- [5] V. Andreoni, Estimating the European CO<sub>2</sub> emissions change due to COVID-19 restrictions, *Sci. Total Environ.* 769 (2021), 145115.
- [6] J.M. Reilly, Y.-H.H. Chen, H.D. Jacoby, The COVID-19 effect on the Paris agreement, *Humanit. Soc. Sci. Commun.* 8 (2021).
- [7] IEA World Energy Outlook, 2020.
- [8] European Union Climate Negotiations, Available online: [https://ec.europa.eu/cli/ma/policies/international/negotiations\\_es](https://ec.europa.eu/cli/ma/policies/international/negotiations_es) (accessed on Feb 24, 2021).
- [9] Ministerio para la Transición Ecológica y el Reto Demográfico Climate Change.
- [10] N. Pardo, G. Penagos, A. González, A. Botero, Calculation of greenhouse gases in the construction sector in the Aburrá Valley, Colombia, in: *Proceedings of the Proceedings of 33rd PLEA International Conference: Design to Thrive, PLEA 2017*, vol. 1, 2017, pp. 932–939.
- [11] Pervez, H.; Ali, Y.; Petrillo, A. A quantitative assessment of greenhouse gas (GHG) emissions from conventional and modular construction: a case of developing country. *J. Clean. Prod.* 2021, 294.
- [12] MITECO Inventario Nacional de emisiones a la atmósfera, Emisiones de Gases de Efecto Invernadero. Serie 1998-2018, 2020, p. 6. Informe resumen.
- [13] V. Alcántara, E. Padilla, Key sectors in greenhouse gas emissions in Spain: an alternative input–output analysis, *J. Ind. Ecol.* 24 (2020) 577–588.
- [14] I. Sartori, A.G. Hestnes, Energy use in the life cycle of conventional and low-energy buildings: a review article, *Energy Build.* 39 (2007) 249–257.
- [15] B. Rosselló-Batlle, A. Moia, A. Cladera, V. Martínez, Energy use, CO<sub>2</sub> emissions and waste throughout the life cycle of a sample of hotels in the Balearic Islands, *Energy Build.* 42 (2010) 547–558.
- [16] T. Huo, H. Ren, X. Zhang, W. Cai, W. Feng, N. Zhou, X. Wang, China's energy consumption in the building sector: a Statistical Yearbook-Energy Balance Sheet based splitting method, *J. Clean. Prod.* 185 (2018) 665–679.
- [17] T. Wang, S. Seo, P.C. Liao, D. Fang, GHG emission reduction performance of state-of-the-art green buildings: review of two case studies, *Renew. Sustain. Energy Rev.* 56 (2016) 484–493.
- [18] Ministerio de Fomento (España) Documento Básico HE Ahorro de Energía 2019, Código Técnico la Edif, 2019, pp. 1–129.
- [19] D. Kairies-Alvarado, C. Muñoz-Sanguinetti, A. Martínez-Rocamora, Contribution of energy efficiency standards to life-cycle carbon footprint reduction in public buildings in Chile, *Energy Build.* 236 (2021), 110797.
- [20] A.E. Fenner, C.J. Kibert, J. Woo, S. Morque, M. Razkenari, H. Hakim, X. Lu, The carbon footprint of buildings: a review of methodologies and applications, *Renew. Sustain. Energy Rev.* 94 (2018) 1142–1152.
- [21] X.J. Li, J. Yu Lai, C. Yun Ma, C. Wang, Using BIM to research carbon footprint during the materialization phase of prefabricated concrete buildings: a China study, *J. Clean. Prod.* 279 (2021), 123454.
- [22] X.J. Li, Y. Zheng, Dan using LCA to research carbon footprint for precast concrete piles during the building construction stage: a China study, *J. Clean. Prod.* 245 (2020), 118754.



- [23] G. Sánchez-Barroso, M. Botejara-Antúnez, J. García-Sanz-Calcedo, F. Zamora-Polo, A life cycle analysis of ionizing radiation shielding construction systems in healthcare buildings, *J. Build. Eng.* 41 (2021), 102387.
- [24] G. Sánchez-Barroso, J. González-Domínguez, J. García-Sanz-Calcedo, M. Sokol, Impact of weather-influenced urban mobility on carbon footprint of Spanish healthcare centres, *J. Transport Health* (2021) 20.
- [25] X. Yang, M. Hu, J. Wu, B. Zhao, Building-information-modeling enabled life cycle assessment, a case study on carbon footprint accounting for a residential building in China, *J. Clean. Prod.* 183 (2018) 729–743.
- [26] J. Xiao, C. Wang, T. Ding, A. Akbarnezhad, A recycled aggregate concrete high-rise building: structural performance and embodied carbon footprint, *J. Clean. Prod.* 199 (2018) 868–881.
- [27] F. Scrucca, C. Ingraio, C. Maalouf, T. Moussa, G. Polidori, A. Messineo, C. Arcidiacono, F. Asdrubali, Energy and carbon footprint assessment of production of hemp hurds for application in buildings, *Environ. Impact Assess. Rev.* 84 (2020), 106417.
- [28] A.R. Gamarra, I.R. Istrate, I. Herrera, C. Lago, J. Lizana, Y. Lechón, Energy and water consumption and carbon footprint of school buildings in hot climate conditions. Results from life cycle assessment, *J. Clean. Prod.* 195 (2018) 1326–1337.
- [29] R. Clabeaux, M. Carbajales-Dale, D. Ladner, T. Walker, Assessing the carbon footprint of a university campus using a life cycle assessment approach, *J. Clean. Prod.* 273 (2020), 122600.
- [30] N.C. Onat, M. Kucukvar, O. Tatari, Scope-based carbon footprint analysis of U.S. residential and commercial buildings: an input-output hybrid life cycle assessment approach, *Build. Environ.* 72 (2014) 53–62.
- [31] Z. Wang, Y. Duan, Y. Jin, Z.-J. Zheng, Coronavirus disease 2019 (COVID-19) pandemic: how countries should build more resilient health systems for preparedness and response, *Glob. Health J.* 4 (2020) 139–145.
- [32] F. McGain, C. Naylor, Environmental sustainability in hospitals – a systematic review and research agenda, *J. Health Serv. Res. Pol.* 19 (2014) 245–252.
- [33] M.J. Eckelman, J.D. Sherman, A.J. MacNeill, Life cycle environmental emissions and health damages from the Canadian healthcare system: an economic-environmental-epidemiological analysis, *PLoS Med.* 15 (2018).
- [34] M. Ali, W. Wang, N. Chaudhry, Application of life cycle assessment for hospital solid waste management: a case study, *J. Air Waste Manag. Assoc.* 66 (2016) 1012–1018.
- [35] Nansai, K.; Fry, J.; Malik, A.; Takayanagi, W.; Kondo, N. Carbon footprint of Japanese health care services from 2011 to 2015. *Resour. Conserv. Recycl.* 2020, 152.
- [36] CYPE Ingenieros S.A., Software de CYPE Ingenieros para Arquitectura, Ingeniería y Construcción, Available online: <http://programas.cype.es/>.
- [37] Autodesk Inc, Revit Software de BIM multidisciplinar para diseños coordinados de mayor calidad. Available online: <https://www.autodesk.es/products/revit/overview?term=1-YEAR&support=null>.
- [38] UNE UNE-EN ISO 14067 Gases de efecto invernadero, Huella de carbono de productos. Requisitos y directrices para cuantificación (ISO 14067:2018), Aenor, 2019.
- [39] Ministerio de Fomento Documento Básico SE, Seguridad estructural, Código Técnico la Edif, 2019, pp. 1–39.
- [40] A. Pedreño Manresa, Desarrollo de una aplicación para el cálculo de la huella de carbono en proyectos de construcción, 2015.
- [41] A. Yörükoğlu, F. Akkurt, S. Çulha, Investigation of boron usability in rock wool production, *Construct. Build. Mater.* 243 (2020), 118222.
- [42] Z. Prošek, J. Trejbal, V. Nežerka, V. Goliáš, M. Faltus, P. Tesárek, Recovery of residual anhydrous clinker in finely ground recycled concrete, *Resour. Conserv. Recycl.* 155 (2020), 104640.
- [43] M. Yamashita, T. Harada, E. Sakai, K. Tsuchiya, Influence of sulfur trioxide in clinker on the hydration heat and physical properties of Portland cement, *Construct. Build. Mater.* 250 (2020), 118844.
- [44] A.P. Fantilli, O. Mancinelli, B. Chiaia, The carbon footprint of normal and high-strength concrete used in low-rise and high-rise buildings, *Case Stud. Constr. Mater.* 11 (2019), e00296.
- [45] E.A. Piñero, Repercusión medioambiental del uso de la cerámica estructural en España. Energía embebida y huella de carbono, Universidad Politécnica de Madrid, 2014.